

Main

Product or component type	Communication card
Range compatibility	Altivar 61 Altivar 71 Altivar 71Q Altivar 61Q
Communication port protocol	Modbus TCP
Product specific application	For daisy chain mounting
Connector type	1 RJ45
Transmission rate	100 Mbps 10 Mbps
Physical interface	Ethernet 2
Web services	Altivar viewer Ethernet statistics Altivar chart IO Scanner FDR Agent Data editor E-mail Security

Complementary

Exchange mode	Half duplex and full duplex
Communication data link	LLC : IEEE 802.2 MAC : IEEE 802.3
Communication network type	IP conforming to RFC791
Communication transport type	UDP 8 connections maximum TCP conforming to RFC793
Concept	Transparent Ready class C20
Web server	Embedded
Communication service	CiA 402 profile I/O profile Communication monitoring can be inhibited, adjustable Diagnostics (08) FTP I/O scanning service can be inhibited Read device identification (43) Read holding registers (03)

	Read input registers (04) Read/write multiple registers (23) SNMP TFTP Write multiple registers (16) Write single register (06)
Display type	1 LED for 10/100 Mbps (speed) 1 LED for FLT (Ethernet fault) 1 LED for RX (reception) 1 LED for STS (IP address) 1 LED for TX (transmission) Graphic display terminal for control word received Graphic display terminal for reference received Web server
Net weight	0.3 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------

VW3A3310D is replaced by:



Options VW3A3320

EtherNet/IP communication card - 2 RJ 45 connectors

Qty 1

Reason for Substitution: Rebranding | Substitution date: 02 November 2016